


## **ENVR**

In The Box Marketing Images Installation Guide





## ∧ Overview

481.4 x 480 x 132 mm Dimensions (19 x 18.9 x 5.2")

UniFi Application Suite

Protect Access

(210) HD (140) 2K Managed Cameras (70) 4K

Managed Access Hubs

Storage Capacity

Data Protection Vantage Point

(2) 10G SFP+ ports Networking Interface (1) 10 GbE RJ45 port

Power Redundancy

Form Factor Rack Mount (3U)

Door Access Support

(16) 2.5/3.5" HDD / SSD support Hard Drive Capacity

Max. Power Budget for Drives 310W Max. Power Consumption 410W

(2) AC input, 100—240V, 7A Max., 50/60Hz (Redundant, hot-swappable)

Hot-swappable 550W CRPS Power Supply Processor 8-core ARM® at 2.5 GHz

32 GB Memory Display Bezel (Optional)

Without rails: 16.6 kg (36.6 lb) With rails: 19.5 kg (43.0 lb) Weight

Enclosure Material SGCC steel Mount Material

Slide Rails

Posts depths ranging from 650 to 1,000 mm (25.6–39.4")

Ambient Operating Temperature -5 to 40° C (23 to 104° F) Ambient Operating Humidity 5 to 95% noncondensing

NDAA Compliant

Certifications CE, FCC, IC