

UniFi

DATASHEET

U7 Pro

Datasheet

In The Box

Marketing Images

FAQ

Installation Guide



Overview

Dimensions	Ø206 x 46 mm (Ø8.1 x 1.8")
WiFi Standard	WiFi 7
Spatial Streams	6
Coverage Area	140 m ² (1,500 ft ²)
Max. Client Count	300+
Uplink	2.5 GbE
Mounting	Ceiling, Wall (Pro Mount Included)
Power Method	PoE+

Performance

MIMO	
6 GHz	2 x 2 (DL/UL MU-MIMO)
5 GHz	2 x 2 (DL/UL MU-MIMO)

Passpoint (Hotspot 2.0)	✓
Captive Hotspot Portal	
Custom Branding Landing Page	✓
Voucher Authentication	✓
Payment-Based Authentication	✓
External Portal Server Support	✓
Password Authentication	✓
Guest Network Isolation	✓
Private Pre-Shared Key (PPSK)	✓
WiFi Speed Limiting	✓
Client Device Isolation	✓
WiFi Schedules	✓
RADIUS over TLS (RadSec)	✓
Dynamic RADIUS-assigned VLAN	✓

Hardware

Max. Power Consumption	21W
Supported Voltage Range	44—57V DC
Networking Interface	(1) 1/2.5 GbE RJ45 port
Weight	680 g (1.5 lb)
Management	Ethernet
Enclosure Material	Polycarbonate, metal
Mount Material	Stainless steel (SUS304), galvanized steel (SGCC)
LEDs	
System	White/Blue
Channel Bandwidth	HT 20/40, VHT 20/40/80/160, HE 20/40/80/160, EHT 20/40/80/160/240/320 (MHz)
NDAA Compliant	✓
Certifications	CE, FCC, IC, Anatel: 06370-24-08356 US/CA: 2400 - 2472 MHz

2.4 GHz	2 x 2 (DL/UL MU-MIMO)
Max. Data Rate	
6 GHz	5.8 Gbps (BW320)
5 GHz	4.3 Gbps (BW240)
2.4 GHz	688 Mbps (BW40)
Antenna Gain	
6 GHz	5.8 dBi
5 GHz	6 dBi
2.4 GHz	4 dBi
Max. TX Power	
6 GHz	23 dBm
5 GHz	26 dBm
2.4 GHz	23 dBm
Max. BSSIDs	8 per Radio
Supported Data Rates	
802.11be (WiFi 7)	7.3 Mbps to 5.8 Gbps (MCS0 - MCS13 NSSI/2, EHT 20/40/80/160/240/320)
802.11ax (WiFi 6/6E)	7.3 Mbps to 2.4 Gbps (MCS0 - MCS11 NSSI/2, HE 20/40/80/160)
802.11ac (WiFi 5)	6.5 Mbps to 1.7 Gbps (MCS0 - MCS9 NSSI/2, VHT 20/40/80/160)
802.11n	6.5 Mbps to 300 Mbps (MCS0 - MCS15, HT 20/40)
Features	
Wireless Meshing	✓
Band Steering	✓
802.11v BSS Transition Management	✓
802.11r Fast Roaming	✓
802.11k Radio Resource Management (RRM)	✓
Advanced Radio Management	✓

Operating Frequency	U-NII-1: 5150 - 5250 MHz U-NII-2A: 5250 - 5350 MHz U-NII-2C: 5470 - 5725 MHz U-NII-3: 5725 - 5850 MHz U-NII-5 to U-NII-8 : 5925 - 7125 MHz
	Worldwide: 2400 - 2483.5 MHz 5150 - 5725 MHz 5925 - 7125 MHz
Ambient Operating Temperature	-30 to 40° C (-22 to 104° F)
Ambient Operating Humidity	5 to 95% noncondensing
Software	
Application Requirements	
UniFi Network	Version 8.0.28 and later