

UVC-G6-Dome

In The Box

Marketing Images Installation Guide











△ Overview

Ø144.7x 96.3 mm (Ø5.7 x 3.8") Dimensions 30 m (98 ft) Face Recognition

License Plate Recognition Smart Detections (People, Vehicles,

Networking Interface 10/100 MbE RJ45 port H: 109.9°, V: 56.7°, D: 134.1°

Microphone Audio Weatherproofing **I**K10 Tamper Resistance

Ceiling, Wall mount (Included) Mounting

Gang Box Mounting Plate, Camera Dual Mount, Flush Mount, Weather Shield (Optional)

∧ Performance

Networking Interface 10/100 MbE RJ45 port

Color, brightness, sharpness, contrast, white balance, exposur Image Settings control, 2DNR, 3DNR, NR by motion, masking, text overlay, H

Max. Frame Rate

8MP 3840 x 2160 (16:9) Resolution

1/1.8" 8MP Sensor Fixed focal length Lens

Night Mode Built-in IR LED illumination and IR cut filter

∧ Hardware

Max. Power Consumption 37—57V DC Supported Voltage Range

Processor Quad-core Arm® Cortex®-A53 based chip

Weight 820 g (1.8 **l**b) Enclosure Material Aluminum allov Mount Material Button (1) Factory-reset

Ambient Operating Temperature -20 to 50° C (-4 to 122° F) Ambient Operating Humidity 0 to 90% noncondensing

NDAA Compliant

Certifications CE, FCC, IC